

Watching brief on advanced fuel cycles and alternative waste management technology

The Nuclear Waste Management Organization (NWMO) developed the Adaptive Phased Management (APM) approach after an extensive study and engagement with Canadians during 2002 to 2005 to identify a long-term management approach for Canada's used nuclear fuel. In considering different methods of managing used nuclear fuel for the long term, Canadians clearly identified their values and priorities as:



- » Safety and security must be our top priority;
- » This generation must take responsibility for the waste it has created;
- » We must use best international practice; and
- » We must have flexibility for future generations to make their own decisions.

The APM approach best meets these values and priorities. It was selected by the Government of Canada in 2007 as Canada's plan. The technical end point of APM requires used nuclear fuel to be safely contained and isolated in a deep geological formation. This is consistent with the policy direction of all countries with major nuclear power programs – even countries that currently practice or advocate various forms of recycling are planning to construct deep geological repositories to manage the resulting long-lived wastes.

During the national study, Canadians expressed interest in knowing more about the possibility of recycling or reusing used nuclear fuel and alternative methods for long-term management of used nuclear fuel. The NWMO's analysis concluded that reprocessing of used fuel was a highly unlikely scenario for Canada at that time. In addition, there were no preferred alternative technical methods. However, the NWMO recommended keeping a watching brief on the status of the technology internationally, and the potential for change in the fuel cycle in Canada.

The NWMO has been maintaining and publishing this watching brief since 2008. This edition of the watching brief paper outlines recent international research and developments in advanced fuel cycles, as well as recent developments in the deep borehole disposal concept. The main conclusions are:

- » There continues to be international interest in new fuel cycles, as well as in the very deep borehole concept, but no technical breakthroughs that change the previous conclusion regarding the APM approach for management of present Canadian used nuclear fuel.
- » The introduction of Small Modular Reactors (SMRs) in Canada will result in small quantities of new nuclear fuel waste types. The impact of these potential new wastes on the NWMO program is evaluated as part of the consideration of the SMR technologies.
- » Advanced fuel cycles considered to date will produce long-lived nuclear fuel waste that would need to be managed by the NWMO in a manner that is safe, socially acceptable, technically sound, environmentally responsible, and economically feasible.
- » The NWMO will continue maintaining our watching brief on developments on advanced fuel cycles and alternative technical methods that could have an impact on Canada's future waste management requirements.

Introduction

The NWMO maintains a watching brief on worldwide developments in advanced fuel cycles, including reprocessing and recycling technologies, as well as alternative technical methods for the long-term management of used nuclear fuel. Previous detailed technical reports [Jackson, 2008-2010] and summary watching brief reports [e.g., NWMO, 2021] are available on the NWMO website.

Research and development work continued in 2022 in various countries and international collaborative programs to assess the technology and implications of advanced fuel cycles, including closed fuel cycles based on reprocessing, partitioning and transmutation (RP&T), and alternative technical methods for the long-term management of used nuclear fuel.

Current fuel cycles

There are three basic nuclear fuel cycles:

- » "Open" or "once through," in which the fuel is irradiated in the reactor, then considered to be waste when it is removed.
- » "Partial recycle" or "twice through," in which the used fuel is reused again. In one version, used fuel is reprocessed to recover plutonium, converted to mixed Pu-U oxide (MOX) fuel and reused once more in a current reactor type (used to some extent in France). In another version, used fuel from a light water reactor (LWR) is considered to be converted into fuel for reuse in a CANDU reactor (planned to be used in China).
- » "Closed" or "full recycle," in which the used fuel is reprocessed to recover fissile isotopes like plutonium and other actinides, and then used in advanced reactors such as fast neutron reactors (FRs). The FR used fuel is then reprocessed and continuously recycled in the FRs to extract additional energy. Depending on the reactor, additional amounts of natural or depleted uranium or reprocessed used fuel can be added to replenish the fuel consumed in the FR.

Other variations can include combinations of conventional thermal reactors, FRs and/or accelerator-driven systems (ADS).

The majority of the commercial nuclear power reactors in operation around the world today are based on thermal (“low energy”) neutrons. These reactors use a moderator material to slow down the high energy neutrons from the fission reactions – the moderators are usually normal or light water (most non-CANDU reactors), heavy water (CANDU reactors) or graphite (gas cooled reactors). The fuels used in these reactors contain either natural uranium (0.7 per cent U-235 and 99.3 per cent U-238) such as in CANDU reactors, or fuel with a higher concentration of fissile U-235 (typically 3 to 5 per cent). Producing this higher U-235 concentration is known as enrichment. Operation of current reactor types requires a continuous supply of fresh uranium as a source of U-235. A byproduct of the enrichment process is depleted uranium, which has a reduced U-235 content of around 0.3 per cent and is now generally considered to be a waste by countries that operate enrichment facilities. However, the depleted uranium from the enrichment process is a potential fuel source for some advanced reactor fuel cycles.

A closed fuel cycle requires a FR in order to effectively use the fuel. FRs do not use a moderator, and FR technology is more complicated. Table 1 lists the currently operating or planned FRs for generating electricity. They can extract energy from U-238, as well as other actinides (plutonium, americium, neptunium, etc.). In the case of U-238, this is done by first converting the U-238 to Pu-239 via neutron capture and subsequent radioactive decay, and then inducing fission in the Pu-239 by another neutron. As the U-238 is consumed, makeup uranium or other actinides can be added, either from reprocessed thermal reactor fuel or from the depleted uranium from enrichment processes. Depleted uranium is widely available, has very low specific radioactivity and can be more easily handled, whereas the reprocessed uranium and other actinides tend to be very radioactive.

Table 1: Fast reactors currently in operation or under construction for generating electricity

Country	Facility	Capacity (MWe)	Status
Russian Federation	BN-600 BN-800	600 880	Operating since 1980 – sodium pool type Operating since 2016 – sodium pool type
India	PFBR	500	Under construction – sodium pool type
China	CFR-600	2 x 600	Under construction – sodium pool type

Canada, as well as most other nuclear power generating countries, currently follows the open fuel cycle. As shown in Table 2, a few countries, notably France, the Russian Federation and India, reprocess some of their fuel, with some of the resulting MOX fuel used in a partial recycle fuel cycle or stored awaiting future recycling in unspecified future reactors. Some countries have reprocessed some fuel in the past, but are no longer doing so now; their reprocessed fuel is being treated as waste. Table 3 shows a summary of global reprocessing capacity for commercial fuels, not including smaller and already closed facilities and facilities used solely for military purposes. It also includes information on the nuclear fuel cycle strategies for countries using CANDU fuel.

Table 2: Summary of current status of reprocessing for the nuclear power fuel cycle

Country	Commercial scale reprocessing facility		Currently send used fuel for reprocessing in other country	Some used fuel reprocessed in past	Planning direct placement of used fuel in a repository
	Existing	Planned			
Belgium				✓	✓
Bulgaria			✓	✓ ⁽⁷⁾	
Canada					✓
China ⁽³⁾		✓			✓ ⁽⁴⁾
Czech Republic				✓ ⁽⁷⁾	✓
Finland				✓ ⁽⁷⁾	✓
France ⁽³⁾	✓ ⁽²⁾				
Germany				✓	✓
Hungary				✓ ⁽⁷⁾	✓
India ⁽³⁾	✓	✓			
Italy			✓		
Japan		✓ ⁽⁶⁾	✓		
Korea, Rep. of					✓
Mexico					✓
Netherlands			✓ ⁽⁵⁾		
Pakistan ⁽³⁾					
Romania					✓
Russian Federation ⁽³⁾	✓	✓			
Slovakia				✓ ⁽⁷⁾	✓
Slovenia					✓
Spain				✓	✓
Sweden				✓	✓
Switzerland				✓	✓
Ukraine				✓ ⁽⁷⁾	✓
United Kingdom ⁽¹⁾				✓	✓
United States ⁽³⁾				✓	✓

(1) The United Kingdom ceased all reprocessing in July 2022.

(2) France supplied commercial reprocessing services to a number of European and Asian countries.

(3) China, France, the United Kingdom, the Russian Federation, the United States, Pakistan, and India currently reprocess, or have reprocessed in the past, for military reasons, as well as for nuclear power plant purposes.

(4) China plans direct placement of its used CANDU fuel in a repository. Some LWR fuel is planned to be reused in its CANDU reactors.

(5) Used fuel sent to France for reprocessing. Contract extended in 2015 to end of life for current reactors.

(6) Commercial scale facility at Rokkasho-mura has been constructed and is undergoing final commissioning test.

(7) Some used fuel was sent to former Soviet Union for reprocessing. Practice terminated in early 1990s.

Table 3: Summary of global reprocessing capacity for commercial fuels

Country	Facility	Capacity (tonnes per year)	Status
China	Gansu	200	Under construction (expected ~2025)
France	UP1, Marcoule	600	Shut down/decommissioning
	UP2-400, La Hague	400	Shut down/decommissioning
	UP2-800, La Hague	800	In operation
	UP3, La Hague	800	In operation
India	Tarapur	100	In operation
	Kalpakkam	100	In operation
Japan	Tokai	90	Shut down/decommissioning
	Rokkasho	800	In commissioning (expected ~2024)
Russian Federation	RT-1, Mayak	400	In operation (expected shut down ~2030)
	MCC-PDC	250	Under construction
	RT-2, Zheleznogorsk	700	Under construction (expected ~2025)
United Kingdom	MAGNOX, Sellafield	1,500	Shut down 2022
	THORP, Sellafield	900	Shut down 2018
United States	West Valley	300	Operated 1966-72, decommissioned

Advanced fuel cycles

The primary interest in advanced fuel cycles is with respect to closed fuel cycles (although partial fuel cycles are currently in limited use). Such advanced fuel cycles are of interest because they use the uranium fuel very efficiently. In particular, some advanced fuel cycles are theoretically almost self-sustainable once they reach equilibrium.

Reducing the need for fresh uranium is the direct benefit. For Canada, with significant uranium resources, this would reduce environmental impact of mining through efficient use of the mined uranium.

A second potential benefit is to reduce the “radiotoxicity” of the waste. This would be achieved by reprocessing the fuel and recycling some or most of the actinides, i.e., uranium and transuranics, into a FR. The actinides are typically long-lived, so consuming them in a FR reduces the burden on the repository needed to handle the remaining long-lived wastes.

A third potential benefit is to reduce the size of the repository by reducing the waste volume, or equivalently to allow one repository to handle a larger nuclear fleet. Uranium constitutes the bulk of the used fuel, so separating and reusing it removes waste volume.

However, there are scientific and engineering challenges with advanced fuel cycles such as development of suitable materials, and the scale up from experiments to full-sized reactors. There are also economic and socio-political challenges, including the costs for development and siting of facilities, and addressing the risk of proliferation. Achieving these benefits assumes that nuclear energy continues to be an economic choice for a given country.

With respect to repository size, recycling of used fuel into FRs can reduce the volume of high-level waste produced per megawatt of electricity generated. This could reduce the amount of repository rock that needs to be excavated per megawatt, but it may not significantly reduce the required footprint area of a repository. This is because the footprint is governed by the total thermal output of the waste, not by its total volume nor by its volume per megawatt. The thermal output of the wastes is primarily driven by how much power has been produced regardless of the fuel cycle. In order to achieve significant reduction in repository footprint, there would also need to be partitioning of the shorter-lived fission products, plus significant duration surface storage for decay of heat generating radionuclides. Even in this case, the reduction in high-level waste repository space may be offset by the increase in the long-lived intermediate-level wastes resulting from these fuel cycles [RED-IMPACT, 2008].

Also, reducing the actinides does not avoid the need for some long-term waste management due to residual actinides and the long-lived fission products. While reducing the long-lived actinides reduces the “radiotoxicity” of the waste and is clearly favorable, it may not significantly improve the overall safety of a repository because the actinide elements have very low mobility in the repository environment. It is the long-lived fission products, such as I-129, that are generally the key radionuclides driving the repository long-term safety [Kessler et al., 2012; Sandia, 2012a; Posiva, 2021; EASAC, 2014; NWMO, 2017, 2018]. These long-lived fission products are generally not reduced in advanced fuel cycles. Furthermore, recycling fuel to generate more electricity means that there will be more fission products produced, approximately proportional to the total power generated, regardless of fuel cycle.

In any event, fully implementing a closed fuel cycle requires the commercial scale deployment of advanced reactors such as FRs, as well as their associated infrastructure such as reprocessing plants and fuel fabrication facilities. Although FRs have been in existence since the 1950s, they have yet to achieve widespread commercial acceptance and deployment (see Table 1). See, for example, [IAEA, 2012, 2013, 2022d] for descriptions of various FR prototypes and their operating histories.

These factors have been reflected in various national reviews, which have continued to support the need for a deep geological repository for used nuclear fuel or high-level wastes. In particular:

- » A 2013 comprehensive review of used fuel management options for Korea concluded: “...no technical justification exists for P&T to be considered an alternative to direct geological disposal, and indeed, no evidence that any of the conventional P&T schemes could, even if they could be implemented, remove the need for deep geological disposal or even make disposal significantly easier or safer” [MII, 2013].
- » The Australian Royal Commission into the Nuclear Fuel Cycle stated that “there is international consensus that deep geological disposal is the best available approach to long-term disposal of used fuel” [Government of South Australia, 2016].
- » The Nuclear Energy Agency (NEA) has stated in its Policy Brief on the disposal of radioactive waste issued in June 2020 that “there is a strong international scientific consensus that deep geological repositories (DGRs) are a safe and effective approach to the permanent disposal of high-level wastes and spent nuclear fuel” [OECD/NEA, 2020a].
- » A recent study in the United States on the merits and viability of different nuclear fuel cycles using advanced reactors, conducted by the National Academies of Sciences, Engineering and Medicine stated that “Most importantly, advanced reactors and their associated fuel cycles would not eliminate the requirement for geologic repositories for some radioactive wastes because even advanced reactors will require disposal of radioactive fission products” [NASEM, 2022].

Technology status for advanced fuel cycles

There continues to be interest in advanced fuel cycles, and progress is being made in the underlying science and technology. Most recent findings were presented in 2022 at various international conferences and technical meetings held in person and virtually, notably:

- » 11th International SMR & Advanced Reactor Summit 2022 (May 2022, Atlanta, United States) [Reuters Events, 2022];
- » GLOBAL 2022 International Conference on Nuclear Fuel Cycle, New Nuclear Perspectives in the Energy Supply Crisis and Climate Emergency (July 2022, Reims, France) [SFEN, 2022];
- » 29th International Conference on Nuclear Engineering, ICONE29 (August 2022, Shenzhen, China) [ICONE, 2022];
- » World Nuclear Association Symposium (September 2022, London, United Kingdom) [WNA, 2022a];
- » TopFuel 2022 (October 2022, Raleigh, United States) [ANS, 2022];
- » GEN IV International Forum (October 2022, Toronto, Canada) [GIF, 2022a];
- » Canadian Nuclear Society's 4th International Conference on Generation IV and Small Reactors (G4SR-4) (October 2022, Toronto, Canada) [CNS, 2022]; and
- » Materials Research Society's Symposium, EN08-Scientific Basis for Nuclear Waste Management (November-December 2022, Boston, United States) [MRS, 2022].

The NWMO monitors these conferences, as well as technical reports published by the Organisation for Economic Co-operation and Development Nuclear Energy Agency (OECD/NEA) [e.g., OECD/NEA, 2011-2021c], International Atomic Energy Agency (IAEA) [e.g., IAEA, 2012-2022e], French Commissariat à l'énergie atomique et aux énergies alternatives (CEA) [e.g., CEA, 2015], United States Nuclear Regulatory Commission [U.S. NRC, 2012], Electric Power Research Institute [e.g., EPRI, 2015-2021], the United Kingdom Radioactive Waste Management agency [RWM, 2017], and various international collaborative projects (such as the European Sustainable Nuclear Energy Technology Platform [SNETP, 2012-2021], the Advanced Fuels for Generation IV Reactors: Reprocessing and Dissolution [ASGARD, 2016], and the GEN IV Integrated Oxide Fuels Recycling Strategies [GENIORS, 2020] projects).

NWMO staff also prepared technical reports and related conference papers outlining the potential impacts of advanced fuel cycles on Canadian used fuel inventories and long-term management needs [NWMO, 2015a,b; Ion, 2016; Gobien, 2016].

Discussion on advanced reactors

Advanced fuel cycles are generally considered in the context of particular reactor concepts, as the reprocessing approach is closely related to the reactor concept.

Work on advanced reactor concepts can be loosely characterized as Generation III+ or Generation IV (GEN-IV), where current commercial power reactors now under construction are considered as Generation III. There is an international GEN-IV collaborative project which is considering several designs, including both thermal reactors and FRs [GIF, 2022b] [IAEA, 2019, 2022d, 2022e]. These advanced reactor concepts typically operate at very high temperatures (typically 400°C or more), and use liquid metals (e.g., sodium or lead), molten salts (e.g., fluoride or chloride mixtures), or gases (helium) as coolants rather than light water or heavy water.

In addition, SMRs have also gained a lot of international interest. The focus of these is on small power output, allowing them to be built in a more modular manner, at lower cost, and potentially used in more places than the conventional 1,000 MWe power reactors. These SMR concepts include both small versions of conventional thermal reactors, as well as FRs.

While there are a large number of SMR concepts that have been proposed worldwide [IAEA, 2022d], the concepts described in Table 4 are currently under consideration in Canada and are at different stages of the Canadian Nuclear Safety Commission's (CNSC) vendor design review. In addition to the SMRs included in Table 4, two vendors (Westinghouse Electric Company, LLC and StarCore Nuclear) have also applied for service agreements with the CNSC to conduct evaluations of their concept designs (eVinci Micro Reactor solid core and heat pipes, and StarCore module high-temperature gas, respectively) [CNSC, 2022].

Table 4: SMRs currently under evaluation in Canada

Reactor	Vendor	Fuel/Coolant	Type	CNSC vendor design review status [CNSC, 2022]
ARC-100	ARC Nuclear Canada Inc.	Metal/Liquid sodium	Fast reactor	Phase 1 complete Phase 2 in progress
MMR-5, MMR-10	Ultra Safe Nuclear Corporation	Coated oxide in SiC pellet/Helium	Thermal reactor	Phase 1 complete Phase 2 in progress Global First Power submitted application for licence to prepare site
SSR	Moltex Energy	Molten salt/ Molten salt	Fast reactor	Phase 1 complete
IMSR	Terrestrial Energy Inc.	Molten salt/ Molten salt	Thermal reactor	Phase 1 complete Phase 2 in progress
Xe-100	X-energy, LLC	Coated oxide in graphite pebble/Helium	Thermal reactor	Phase 2 in progress
BWRX-300	GE-Hitachi Nuclear Energy	UO ₂ /Light water	Thermal reactor	Phase 2 in progress BWRX-300 was selected by OPG for deployment at Darlington site
SMR-160	SMR, LLC (A Holtec International Company)	UO ₂ /Light water	Thermal reactor	Phase 1 complete
NuScale	NuScale Power, LLC	UO ₂ /Light water	Thermal reactor	Phase 2 in progress

In 2020, the Government of Canada has launched Canada's SMR Action Plan, which outlines Canada's plan for development, demonstration and deployment of SMRs for various applications [SMR Action Plan, 2020]. A memorandum of understanding was signed in 2019 between governments of Ontario, Saskatchewan and New Brunswick on collaborating on the development and deployment of SMRs in these provinces. Alberta signed the memorandum of understanding in 2021.

A number of utilities have expressed interest in supporting the development of SMR technologies. A feasibility report, prepared by Ontario Power Generation (OPG), Bruce Power, NB Power and SaskPower, was published in 2021, providing a feasibility assessment of SMR development and deployment in each of the three provinces [OPG, Bruce Power, NB Power and SaskPower, 2021].

OPG resumed in 2020 the planning activities at the Darlington site for hosting a grid-size SMR [OPG, 2020]. In December 2021, OPG announced that it will work together with GE Hitachi Nuclear Energy to deploy a BWRX-300 SMR at the Darlington new nuclear site, which is the only site currently licensed in Canada for new nuclear build [OPG, 2021]. OPG intends to begin non-nuclear site preparation activities for an SMR at Darlington by the end of 2022 and submitted an application to the CNSC for the Licence to Construct in October 2022 [OPG, 2022].

In 2019, Global First Power, Ultra Safe Nuclear Corporation and OPG formed a joint venture to own and operate the Micro Modular Reactor Project at Chalk River [GFP, 2020a]. Global First Power submitted to the CNSC the initial application for a Licence to Prepare Site, and the regulatory review is underway [GFP, 2019a, 2019b]. In 2022, McMaster University, Ultra Safe Nuclear Corporation and Global First Power formed a partnership and signed a Memorandum of Understanding to study the feasibility of deploying a Micro Modular Reactor at McMaster University or an affiliated site [USNC, 2022].

New Brunswick Power is working with Moltex Energy and Advanced Reactor Concepts (ARC) Clean Energy Canada for developing and demonstrating an advanced SMR nuclear energy research cluster [NB Power, 2019].

SaskPower has selected in June 2022 the GE Hitachi Nuclear BWRX-300 SMR for potential deployment in the province [SaskPower, 2022a]. In September 2022, SaskPower identified two areas in Saskatchewan for further study to determine the feasibility of hosting a SMR [SaskPower, 2022b].

Bruce Power and Westinghouse announced an agreement to pursue applications of Westinghouse's proposed eVinci™ micro reactor program within Canada [Bruce Power, 2020]. Bruce Power has also committed to the development of SMR technology, including memorandums of understanding with MIRARCO Mining Innovation and Laurentian University [Bruce Power, 2018a], as well as NuScale Power [Bruce Power, 2018b].

The Canadian Nuclear Laboratories (CNL) is seeking to establish partnerships with vendors of SMR technology to develop, promote and demonstrate the technology in Canada [CNL, 2017]. At present, four proponents are in various stages of CNL's review [CNL, 2019; GFP, 2020b]. CNL has also formed partnerships with SMR vendors to research SMR fuels and advance SMR technology in Canada [CNL, 2020a, 2020b, 2020c, 2020d]. CNL recently issued a call for proposals for the third round of its Canadian Nuclear Research Initiative (CNRI) program, which was established to accelerate the deployment of SMRs and advanced reactors, including SMR design concepts [CNL, 2021].

In 2021, a report was published by the Canadian Standards Association on the role of standards in facilitating deployment of SMRs in Canada [CSA, 2021].

The FR SMR concepts under advanced consideration use metal or salt fuels; the ARC fuel could be U-Zr metal, and the Moltex fuel could be a sodium/plutonium/actinide-chloride or -fluoride mix. The thermal reactor SMR concepts use a uranium-fluoride-based salt as both fuel and coolant (Terrestrial Energy), coated UO₂ encased in SiC pellets (Ultra Safe Nuclear Corporation), coated UO₂ or UC embedded in graphite pebbles (X-energy), or UO₂ (BWRX-300, SMR-160, NuScale). For comparison, current CANDU fuel is UO₂.

Discussion on reprocessing

Advanced fuel cycles require some type of reprocessing. The current commercial reprocessing technology as used in the facilities listed in Table 1 is based on oxide fuels and wet chemistry (the “PUREX” process). The UO_2 used fuel is dissolved in concentrated acids, then subject to a series of chemical steps to separate out (partition) the various constituents. Relatively pure Pu is separated and converted into an oxide that can be mixed with fresh UO_2 to form MOX fuel, which can be reused again in a conventional thermal reactor. Descriptions of the process used can be found in the technical literature, such as [OECD/NEA, 2012b].

Since the used nuclear fuel is highly radioactive, all this needs to be done using remotely operated, heavily shielded equipment and facilities. Even routine maintenance needs to be done remotely due to residual contamination in the equipment. The reprocessing and partitioning steps also result in large volumes of chemically complex wastes. Some of this material can be recycled back into the process, but most eventually end up as secondary radioactive waste that must be stabilized for storage, then ultimately placed in a repository [MIT, 2011; MIRS, 2013].

This is the benchmark for fuel reprocessing and is a relatively expensive process. Some of the ongoing research is aimed at optimizing this process. Two primary options have been under development – hydrometallurgical and electrometallurgical processes. The hydrometallurgical partitioning, also known as solvent extraction process, builds on the current industrial experience. The electrometallurgical or pyroprocessing concept is a non-aqueous approach. Another concept that is less developed is the fluoride volatility process.

The pyroprocessing approach is suitable for metallic and salt fuel. This approach has been employed in prototype FRs in the past (notably the United States Experimental Breeder Reactor program of the 1950s to 1980s [IAEA, 2012]) and has been proposed for other systems, such as Integral Fast Reactors and PRISM [Triplett et al., 2012] and the ARC SMR [Cheng et al., 2018]. While successfully used in demonstration tests, pyroprocessing has not yet achieved commercial scale implementation. (See, for example, [IAEA, 2021], and Iizuka et al. in [OECD/NEA, 2012a].) Korea had been conducting studies for demonstration at laboratory and engineering scale [OECD/NEA, 2019c].

Moltex Energy proposes to use a form of pyroprocessing, called WATSS (Waste To Stable Salts), to convert spent oxide fuel to a salt form suitable for its Stable Salt Reactor (SSR). A particular feature of its SSR concept is that it is more tolerant of actinides present in the fuel, which means that the reprocessing does not need to deliver a highly purified product, which in turn simplifies the design. Currently, research and planning for development and inactive demonstration of the WATSS process is underway.

In order to be successfully deployed on a commercial basis, the life cycle cost of producing electricity with advanced reactors and reprocessing must be lower than for other electricity production methods, including current nuclear power plants and non-nuclear technologies. A study published in 2013 by the OECD NEA [OECD/NEA, 2013a] looked at life cycle costs for various fuel cycle options and concluded that the once-through fuel cycle was the least expensive at that time. The life cycle costs include development, construction, operation, maintenance, decommissioning, and waste management related costs both for the power plant and for the associated fuel cycle facilities and transportation systems. Another study published by Idaho National Laboratory in 2017 provided the comprehensive set of cost data, along with processes and structures, in support of the United States Department of Energy’s ongoing evaluation of the advanced nuclear fuel cycles [INL, 2017].

A technical study commissioned by the Ontario Government [CNL, 2016] examined the recycling of Ontario's CANDU reactor used fuel under various scenarios, including reusing fuel in the current CANDU reactor fleet and various FR scenarios. The study showed that all the recycling options had a higher life cycle cost than the current reference plan of emplacing the used CANDU fuel in a deep geological repository, significant initial investment costs, and significant social and technical challenges. In addition, they resulted in the production of significant amounts of long-lived, heat-generating radioactive wastes that required emplacement in a deep geological repository.

Many of the studies point out that as an alternative to reprocessing the used nuclear fuel from current reactors, there is sufficient depleted uranium available (from LWR fuel enrichment) to sustain advanced reactors globally for many centuries. This uranium is relatively low radioactivity and easier to handle. About 1.2 million tonnes of depleted uranium are currently stockpiled around the world. Also, the use of enriched uranium could substitute for recycled plutonium at least in the short term [WNA, 2022b].

Discussion on transmutation

The transmutation of actinides into less radioactive or stable elements can also be carried out in an ADS, where high-energy neutrons produced by an accelerator are directed at a blanket assembly containing the waste (actinide elements) along with fissionable fuel. Unlike a nuclear reactor, this is a sub-critical system: the nuclear reaction stops when the accelerator is turned off. An alternative proposal uses a high-power, short-pulse laser as the particle accelerator. An ADS can potentially accept a wide isotopic mix in the blanket assembly, providing very efficient transmutation of actinides and some other long-lived radionuclides.

Significant electrical power is required to generate the neutrons. Some research is underway in Europe, Japan and elsewhere to develop ADS technology. However, the technology has not yet advanced much beyond the theoretical stage, and the availability of continuous high-power neutron beams is currently a key limiting factor. Research results are reported at scientific conferences and meetings such as OECD NEA's 4th International Workshop on Technology and Components of Accelerator-Driven Systems [OECD/NEA, 2019a].

Very deep borehole disposal

A proposed alternative waste management approach is placing the used fuel in very deep boreholes. The concept consists of placing the waste containers at depths greater than 1 kilometre in individual boreholes drilled from the surface. Within each borehole, waste packages would be stacked on top of each other over some distance. With the waste in place, the borehole would be backfilled and sealed to the surface. With the waste placed at this depth, further away from the biosphere than in the mined repository concept, the long-term safety of the system would rest primarily on the separation of the hydrogeological regime at the depth of the waste packages from that near the surface, and on the integrity of the borehole plugs and seals.

To date, a number of studies have suggested that very deep boreholes could potentially have a number of technical advantages compared to mined geologic repositories for certain high-level waste types, such as potential for greater isolation of waste and reduced mobility of radionuclides by increasing the depth, as well as modularity because the disposal capacity can be expanded relatively easily by drilling additional boreholes once a suitable area has been identified and licensed.

The very deep borehole concept has been studied as an alternative to mined deep geological repositories in the United States [Sandia, 2009-2019; U.S. BRC, 2012; U.S. NWTRB, 2016; Deep Isolation, 2020], Sweden [SKB, 1989-2013c; KASAM, 2007], the United Kingdom [NIREX, 2004], and elsewhere [von Hippel and Hayes, 2010; Chapman, 2013]. A 2020 study by the Electric Power Research Institute investigated the feasibility of co-locating a deep borehole disposal with an advanced reactor located on the same site in the United States [EPRI, 2020].

The concept of very deep boreholes is considered for underground disposal of small inventories of intermediate- and high-level radioactive waste [IAEA, 2017c, 2020d; ARPANSA, 2008]. Australia is presently considering borehole disposal for intermediate-level waste [ARPANSA, 2020], and Estonia and Slovenia are considering the concept for disposal of used fuel from SMRs and research reactors, respectively [WNN, 2021a, 2021b].

The United States Department of Energy (U.S. DOE) began studies in 2009 on the very deep borehole concept for disposal of spent fuel assemblies from U.S. nuclear power reactors. Initial studies published by Sandia National Laboratories presented a preliminary evaluation of the concept [Sandia, 2009] and a reference design [Sandia, 2011a,b]. In this design, the waste is assumed to be placed in the lower 1- to 2-kilometre portion of an approximately 3- to 5-kilometre deep borehole, about 45 centimetres in diameter, vertically drilled through overlying rock into crystalline basement rock. Although retrievability would be maintained during placement operations, retrievability of the waste after borehole sealing is assumed not to be required.

In 2014, the U.S. DOE initiated a project to drill a test deep borehole to evaluate the technology for specific types of small-sized, high-activity wastes (such as concentrated Cs and Sr capsules currently stored on the Hanford site) [Sandia, 2014b; U.S. DOE, 2014a,b; U.S. NWTRB, 2016]. The Deep Borehole Field Test Program involved the design, siting and construction of at least one full-sized, non-radioactive deep borehole to a depth of 5 kilometres [Sandia, 2012c, 2015a,b]. A preliminary generic safety case was developed, supporting the feasibility of the concept for disposal of Cs and Sr capsules [Sandia, 2016, 2019]. In 2016, the U.S. DOE announced that a 20-acre site on state-owned land near Rugby, North Dakota, was the preferred site [U.S. DOE, 2016]. However, even though the proposal did not involve the actual disposal of radioactive waste, it was met with extensive local opposition, and a drilling licence was not issued. The project was discontinued in 2017 [U.S. DOE, 2017].

An alternative concept has also been proposed based on disposal of radioactive waste in less deep horizontal boreholes, to potentially impose less stress on the waste packages and allow retrievability. The concept consists of a borehole that would be drilled vertically from the surface, through the sedimentary, igneous or metamorphic rock, to a depth of about 1 kilometre, after which the borehole would then be turned sub-horizontal [Deep Isolation, 2020]. Several long, sub-horizontal boreholes would be used to contain the radioactive waste packages. A private nuclear waste disposal company in the United States, Deep Isolation, proposes to use existing directional drilling technologies, and performed in 2019 a public demonstration test of this concept by placing and retrieving a prototype canister from an existing deep horizontal borehole at about 600 metres underground [Deep Isolation, 2019].

While the concept of very deep disposal for used fuel is considered to be technically feasible, there are some significant challenges to the approach, such as:

- » Drilling of boreholes of the required diameter to the required depth;
- » Controlled emplacement of waste packages at depth (e.g., engineering challenges regarding the limitations of the sizes of the used fuel containers/packages, as well as challenges concerning how to recover if a package gets “stuck” in the borehole before it reaches the intended depth);
- » Development of robust monitoring technology over an extensive area and depth;
- » Development of reliable borehole seals that can be remotely placed from surface; and
- » After waste packages are sealed in place, retrieval would be very difficult.

Overall, the United States Nuclear Waste Technical Review Board [U.S. NWTRB, 2016] concluded that even if deep boreholes proved feasible for certain waste types, they will not eliminate the need for a conventional mined geologic repository. In addition, they concluded that the time required to site, license and develop a deep borehole disposal facility would be comparable to that needed for a conventional mined repository.

The NWMO will continue to monitor the deep boreholes concept as part of our ongoing review of the APM approach.

Conclusions

The NWMO continues to monitor developments in the area of advanced fuel cycles and alternative methods for long-term waste management.

The main conclusions from the NWMO perspective are:

- » There continues to be international interest in new fuel cycles, as well as in the very deep borehole concept, but no technical breakthroughs that change the previous conclusion regarding the APM approach for management of present Canadian used nuclear fuel.
- » The introduction of SMRs in Canada will result in small quantities of new nuclear fuel waste types. The impact of these potential new wastes on the NWMO program is evaluated as part of the consideration of the SMR technologies.
- » Advanced fuel cycles considered to date will produce long-lived nuclear fuel waste that would need to be managed by the NWMO in a manner that is safe, socially acceptable, technically sound, environmentally responsible, and economically feasible.
- » The NWMO will continue maintaining our watching brief on developments on advanced fuel cycles and alternative technical methods that could have an impact on Canada's future waste management requirements.

References

- ANS, 2022. TopFuel 2022, Light Water Reactor Fuel Performance Conference, October 9-13, 2022, Raleigh, NC, United States.
(www.ans.org/meetings/topfuel2022)
- ARPANSA, 2008. Predisposal Management of Radioactive Waste. Australian Radiation Protection and Nuclear Safety Agency Safety Guide, Radiation Protection Series No. 16, August 2008.
(www.arpansa.gov.au/sites/default/files/legacy/pubs/rps/rps16.pdf)
- ARPANSA, 2020. Australian National Report to the Joint Convention Seventh Review Meeting, October 2020.
(www.arpansa.gov.au/sites/default/files/7th_national_report_to_the_joint_convention.pdf)
- ASGARD, 2016. Final Report Summary – ASGARD (Advanced Fuels for Generation IV Reactors: Reprocessing and Dissolution), Sweden.
(www.asgardproject.eu)
- Bruce Power, 2018a. “Bruce Power signs \$1 million MOU for sustainable energy research group,” Bruce Power news release, April 6, 2018.
(www.brucepower.com)
- Bruce Power, 2018b. “Bruce and NuScale collaborate on Canadian SMR business case,” Bruce Power news release, November 27, 2018.
(www.brucepower.com)
- Bruce Power, 2020. “Bruce Power and Westinghouse collaborate to advance application of eVinci™ battery technology to support Canada’s Net Zero initiative,” Bruce Power news release, October 10, 2020.
(www.brucepower.com)
- CEA, 2015. Avancées des recherches sur la séparation-transmutation et le multi-recyclage du plutonium dans les réacteurs à flux de neutrons rapides. Report prepared by CEA, June 2015.
(www.cea.fr)
- Chapman, 2013. Deep Borehole Disposal of Spent Fuel and Other Radioactive Wastes. Report prepared for The Nautilus Institute by Neil A. Chapman, July 2013.
(www.nautilus.org)
- Cheng et al., 2018. Phenomena Important in Liquid Metal Reactor Simulations. Report prepared for the U.S. Nuclear Regulatory Commission by Lap-Yan Cheng, Michael Todosow and David Diamond, BNL-207816-2018-INRE, August 2018.
(www.nrc.gov/docs/ML1829/ML18291B305.pdf)
- CNL, 2016. A Feasibility Study on the Recycling of Used CANDU Fuel, report # 153-124900-REPT-002. Prepared by CNL, April 2016.
(www.ontarioenergyreport.ca)
- CNL, 2017. Small Modular Reactor Technology.
(www.cnl.ca/clean-energy/small-modular-reactors)
- CNL, 2019. “Technology developers advance in CNL’s process to site a small modular reactor,” CNL news release, July 29, 2019.
(www.cnl.ca)
- CNL, 2020a. “CNL & USNC partner on SMR fuel research,” CNL news release, February 26, 2020.
(www.cnl.ca)
- CNL, 2020b. “Canadian Nuclear Laboratories and NB Power sign collaboration agreement to advance small modular reactors,” CNL news release, February 27, 2020.
(www.cnl.ca)

CNL, 2020c. "CNL & Moltex Energy partner on SMR fuel research," CNL news release, April 23, 2020.
(www.cnl.ca)

CNL, 2020d. "CNL and Terrestrial Energy partner on SMR fuel research," CNL news release, September 15, 2020.
(www.cnl.ca)

CNL, 2021. "CNL issues call for proposals for Canadian Nuclear Research Initiative," CNL news release, September 29, 2021.
(www.cnl.ca)

CNS, 2022. 4th International Conference on Generation IV and Small Reactors (G4SR-4), October 3-6, 2022, Toronto, Canada.
(g4sr.org)

CNSC, 2022. Pre-Licensing Vendor Design Review.
(www.nuclearsafety.gc.ca/eng/reactors/power-plants/pre-licensing-vendor-design-review)

CSA, 2021. The Role of Standards in Facilitating Deployment of SMRs in Canada. Report produced by Hatch Ltd. for the Canadian Standards Association, August 2021.
(www.csagroup.org)

Deep Isolation, 2019. "Private company successfully demonstrates deep geologic disposal of prototype nuclear waste canister," Deep Isolation press release, January 16, 2019.
(www.deepisolation.com)

Deep Isolation, 2020. Spent Nuclear Fuel Disposal in a Deep Horizontal Drillhole Repository Sited in Shale: Numerical Simulations in Support of a Generic Post-Closure Safety Analysis. Report prepared by Deep Isolation, Inc. DI-2020-01-R0, May 2020.
(www.deepisolation.com/technology/nuclear-waste-disposal-safety-calculations)

EASAC, 2014. Management of Spent Nuclear Fuel and its Waste. EASAC policy report # 23, prepared by the European Academies' Science Advisory Council, July 2014.
(www.easac.eu)

EPRI, 2015. Program on Technology Innovation: Technology Assessment of a Molten Salt Reactor Design. Electric Power Research Institute Report # 3002005460, October 2015.
(www.epri.com)

EPRI, 2016. Program on Technology Innovation: Assessment of Nuclear Fuel Cycle Simulation Tools. Electric Power Research Institute Report # 3002008044, November 2016.
(www.epri.com)

EPRI, 2017. Program on Technology Innovation: Dynamic Nuclear Fuel Cycle Modeling for Evaluating Liquid-Fueled Molten Salt Reactor Designs. Electric Power Research Institute Report # 3002010474, September 2017.
(www.epri.com)

EPRI, 2020. Feasibility of Borehole Co-Location with Advanced Reactors for Onsite Management of Spent Nuclear Fuel. Electric Power Research Institute Report # 3002019751, December 2020.
(www.epri.com)

EPRI, 2021. Evaluation of Chloride Fuel Salt Lifetime in a Fast-Spectrum, Liquid-Fuel Molten Salt Reactor, Electric Power Research Institute Report # 3002021038, December 2021.
(www.epri.com)

GENIORS, 2020. Gen IV Integrated Oxide Fuels Recycling Strategies.
(www.geniors.eu)

- GFP, 2019a. Licence to Prepare Site Initial Application: MMR Nuclear Plant at Chalk River. Global First Energy Report CRP-LIC-01-002. Global First Energy Document CRP-LIC-01-001, June 2019.
(www.globalfirstpower.com)
- GFP, 2019b. Project Description for the Micro Modular Reactor™ Project at Chalk River. Global First Energy Document CRP-LIC-01-001, July 2019.
(www.globalfirstpower.com)
- GFP, 2020a. “GFP, USNC and OPG form joint venture to own, operate Micro Modular Reactor Project at Chalk River,” GFP news release, June 9, 2020.
(www.globalfirstpower.com)
- GFP, 2020b. “Canada’s first Small Modular Reactor Project achieves new milestone. Signing of project host agreement cements Global First Power as leading SMR project in Canada,” GFP news release, November 18, 2020.
(www.globalfirstpower.com)
- GIF, 2022a. Gen IV Industry Forum, October 3-7, 2022, Toronto, Canada.
(www.gen-4.org)
- GIF, 2022b. Generation IV International Forum.
(www.gen-4.org)
- Gobien, 2016. Some Implications of Recycling Used CANDU Fuel in Fast Reactors, paper prepared by M. Gobien, NWMO, presented at 14th Information Exchange Meeting on Actinide and Fission Product Partitioning and Transmutation, organized by the OECD NEA, September 6-9, 2016, San Diego, United States.
(www.oecd-nea.org/pt/iempt14)
- Government of South Australia, 2016. Royal Commission Report into the Nuclear Fuel Cycle, May 2016.
(yoursay.sa.gov.au/pages/nuclear-fuel-cycle-royal-commission-report-release)
- IAEA, 2012. Status of Fast Reactor Research and Technology Development. Report # IAEA-TECDOC-1691, prepared by the IAEA, December 2012.
(www.iaea.org)
- IAEA, 2013. Design Features and Operating Experience of Experimental Fast Reactors. Report # NP-T-1.9, prepared by the IAEA, November 2013.
(www.iaea.org)
- IAEA, 2017a. Use of Low Enriched Uranium Fuel in Accelerator Driven Subcritical Systems. Report # IAEA-TECDOC-1821, prepared by the IAEA, August 2017.
(www.iaea.org)
- IAEA, 2017b. Research Reactors for the Development of Materials and Fuels for Innovative Nuclear Energy Systems. Report # NP-T-5.8, prepared by the IAEA, September 2017.
(www.iaea.org)
- IAEA, 2017c. Selection of Technical Solution for the Management of Radioactive Waste. Report # IAEA-TECDOC-1817, prepared by the IAEA, July 2017.
(www.iaea.org)
- IAEA, 2018. Experimental Facilities in Support of Liquid Metal Cooled Fast Reactors. Report # NP-T-1.15, prepared by the IAEA, October 2018.
(www.iaea.org)
- IAEA, 2019. Waste from Innovative Types of Reactors and Fuel Cycles. A Preliminary Study. Report # NW-T-1.7, prepared by the IAEA, July 2019.
(www.iaea.org)

- IAEA, 2020a. Understanding and Prediction of Thermohydraulic Phenomena Relevant to Supercritical Water Cooled Reactors (SCWRs). Report # IAEA-TECDOC-1900, prepared by the IAEA, February 2020.
(www.iaea.org)
- IAEA, 2020b. Passive Shutdown Systems for Fast Neutron Reactors. Report # IAEA-NR-T-1.16, prepared by the IAEA, March 2020.
(www.iaea.org)
- IAEA, 2020c. Challenges for Coolants in Fast Neutron Spectrum Systems. Report # IAEA-TECDOC-1912, prepared by the IAEA, May 2020.
(www.iaea.org)
- IAEA, 2020d. Underground Disposal Concepts for Small Inventories of Intermediate and High Level Radioactive Waste. Report # IAEA-TECDOC-1934, prepared by the IAEA, December 2020.
(www.iaea.org)
- IAEA, 2021. Status and Trends in Pyroprocessing of Spent Nuclear Fuels. Report # IAEA-TECDOC-1967, prepared by the IAEA, August 2021.
(www.iaea.org)
- IAEA, 2022a. Status and Trends in Spent Fuel and Radioactive Waste Management. Nuclear Energy Series No. NW-T-1.14 (Rev. 1), prepared by the IAEA, January 2022.
(www.iaea.org)
- IAEA, 2022b. Modelling and Simulation of the Source Term for a Sodium Cooled Fast Reactor Under Hypothetical Severe Accident Conditions. Report # IAEA-TECDOC-2006, prepared by the IAEA, August 2022.
(www.iaea.org)
- IAEA, 2022c. Near Term and Promising Long Term Options for the Deployment of Thorium Based Nuclear Energy. Report # IAEA-TECDOC-2009, prepared by the IAEA, September 2022.
(www.iaea.org)
- IAEA, 2022d. Advances in Small Modular Reactor Technology Developments, A Supplement to: IAEA Advanced Reactors Information System (ARIS), 2022 Edition, September 2022.
(aris.iaea.org)
- IAEA, 2022e. ARIS – Advanced Reactors Information System, database maintained by the IAEA, December 2022.
(aris.iaea.org)
- ICONE, 2022. 29th International Conference on Nuclear Engineering, organized by the American Society of Mechanical Engineers, the Japanese Society of Mechanical Engineers and the Chinese Nuclear Society, August 8-12, 2022, Shenzhen, China.
(event.asme.org/ICONE-2022)
- INL, 2017. Advanced Fuel Cycle Cost Basis – 2017 Edition. Report # INL/EXT-17-43826, NTRD-FCO-2017-000265 prepared by Idaho National Laboratory for the United States Department of Energy Fuel Cycle Options Campaign, September 2017.
(www.inl.gov)
- Ion, 2016. Some Implications of Recycling Used CANDU Fuel in Fast Reactors, paper prepared by M. Ion, NWMO, presented at 3rd Canadian Conference on Nuclear Waste Management, Decommissioning and Environmental Restoration, organized by the Canadian Nuclear Society, September 11-14, 2016, Ottawa, Canada.
(www.nwmdr2016.org)

- Jackson, 2008. Watching Brief on Reprocessing, Partitioning and Transmutation and Alternative Waste Management Technology – Annual Report 2008. Report prepared for the NWMO by David P. Jackson & Associates Ltd., NWMO TR-2008-22, December 2008.
(www.nwmo.ca)
- Jackson, 2009. Watching Brief on Reprocessing, Partitioning and Transmutation (RP&T) and Alternative Waste Management Technology – Annual Report 2009. Report prepared for the NWMO by David P. Jackson & Associates Ltd., NWMO TR-2009-32, December 2009.
(www.nwmo.ca)
- Jackson, 2010. Watching Brief on Reprocessing, Partitioning and Transmutation (RP&T) and Alternative Waste Management Technology – Annual Report 2010. Report prepared for the NWMO by David P. Jackson & Associates Ltd., NWMO TR-2010-24, December 2010.
(www.nwmo.ca)
- KASAM, 2007. Deep boreholes: An alternative for final disposal of spent nuclear fuel? Report 2007:6e from the Swedish National Council for Nuclear Waste, December 2007.
(www.karnavfallsradet.se)
- Kessler et al., 2012. “Radiotoxicity Index”: An Inappropriate Discriminator for Advanced Fuel Cycle Technology Selection. Paper # 12276, prepared by John Kessler, Michael Apted, Matthew Kozak, Mark Nutt, Andrew Sowder, and Peter Swift at Waste Management 2012 Conference, February 26-March 1, 2012, Phoenix, Arizona, United States.
(www.wmsym.org)
- MIIS, 2013. The Bigger Picture: Rethinking Spent Fuel Management in South Korea. James Martin Center for Nonproliferation Studies, Monterey Institute of International Studies, Occasional Paper No. 16, March 2013.
(cns.miis.edu/opapers/pdfs/130301_korean_alternatives_report.pdf)
- MIT, 2011. The Future of the Nuclear Fuel Cycle – An Interdisciplinary MIT Study. Massachusetts Institute of Technology, April 2011.
(energy.mit.edu/wp-content/uploads/2011/04/MITEI-The-Future-of-the-Nuclear-Fuel-Cycle.pdf)
- MRS, 2022. Materials Research Society’s Symposium, EN08-Scientific Basis for Nuclear Waste Management (November/December 2022), Boston, United States.
(www.mrs.org/meetings-events/fall-meetings-exhibits/2022-mrs-fall-meeting)
- NASEM, 2022. Merits and Viability of Different Nuclear Fuel Cycles and Technology Options and the Waste Aspects of Advanced Nuclear Reactors, National Academies of Sciences, Engineering, and Medicine Consensus Study Report, Washington, DC.
(nap.nationalacademies.org)
- NB Power, 2019. “NB Power pleased with progress on Small Modular Reactor work,” New Brunswick Power news release, July 25, 2019.
(www.nbpower.com)
- NIREX, 2004. A Review of the Deep Borehole Disposal Concept for Radioactive Waste. Report prepared by Safety Assessment Management Ltd. for the United Kingdom Nirex. Nirex Report N/108, June 2004.
(www.nda.gov.uk)
- NWMO, 2015a. Some Implications of Recycling CANDU Used Fuel in Fast Reactors, NWMO Technical Report NWMO-TR-2015-11, December 2015.
(www.nwmo.ca)
- NWMO, 2015b. Preliminary Hazard Assessment of Waste from an Advanced Fuel Cycle, NWMO Technical Report NWMO-TR-2015-22, December 2015.
(www.nwmo.ca)

- NWMO, 2017. Postclosure Safety Assessment in a Used Fuel Repository in Crystalline Rock. NWMO Technical Report NWMO TR-2017-02, December 2017.
(www.nwmo.ca)
- NWMO, 2018. Postclosure Safety Assessment in a Used Fuel Repository in Sedimentary Rock. NWMO Technical Report NWMO-TR-2018-08, December 2018.
(www.nwmo.ca)
- NWMO, 2021. Watching brief on advanced fuel cycles and alternative waste management technology – 2021 update.
(www.nwmo.ca)
- OECD/NEA, 2011. Potential Benefits and Impacts of Advanced Nuclear Fuel Cycles with Actinide Partitioning and Transmutation, Report # 6894, prepared by the OECD NEA, September 2011.
(www.oecd-nea.org)
- OECD/NEA, 2012a. Homogeneous Versus Heterogeneous Recycling of Transuranics in Fast Nuclear Reactors. Report # 7077, prepared by the OECD NEA, December 2012.
(www.oecd-nea.org)
- OECD/NEA, 2012b. Spent Nuclear Fuel Reprocessing Flowsheet. Report # NEA/NSC/WPFC/DOC(2012)15, prepared by the OECD NEA, June 2012.
(www.oecd-nea.org)
- OECD/NEA, 2013a. The Economics of the Back End of the Nuclear Fuel Cycle. Report # 7061, prepared by the OECD NEA, September 2013.
(www.oecd-nea.org)
- OECD/NEA, 2013b. Transition Towards a Sustainable Nuclear Fuel Cycle. Report # 7133, prepared by the OECD NEA, July 2013.
(www.oecd-nea.org)
- OECD/NEA, 2015a. Review of Integral Experiments for Minor Actinide Management, Report # 7222, prepared by the OECD NEA, February 2015.
(www.oecd-nea.org)
- OECD/NEA, 2015b. Introduction of Thorium in the Nuclear Fuel Cycle, Report # 7224, prepared by the OECD NEA, June 2015.
(www.oecd-nea.org)
- OECD/NEA, 2016. Small Modular Reactors: Nuclear Energy Market Potential for Near-term Deployment. Report # 7213 prepared by the OECD NEA, September 2016.
(www.oecd-nea.org)
- OECD/NEA, 2018. State-of-the-Art Report on the Progress of Nuclear Fuel Cycle Chemistry. Report # 7267 prepared by the OECD NEA, 2018.
(www.oecd-nea.org)
- OECD/NEA, 2019a. 4th International Workshop on Technology and Components of Accelerator-Driven Systems (TCADS-4), October 14-17, 2019, Antwerp, Belgium.
(www.oecd-nea.org)
- OECD/NEA, 2019b. Proceedings of the Nuclear Energy Agency International Workshop on Chemical Hazards in Fuel Cycle Facilities Nuclear Processing. Workshop organized by OECD NEA, April 17-19, 2018, Boulogne-Billancourt, France. NEA/CSNI/R(2019)9 and NEA/CSNI/R(2019)9/ADD1, May 2019.
(www.oecd-nea.org)

- OECD/NEA, 2019c. Review of Operating and Forthcoming Experimental Facilities Opened to International R&D Co-operation in the Field of Advanced Fuel Cycles. Report #NEA/NSC/R(2018)4 prepared by Nuclear Energy Agency, Nuclear Science Committee, February 2019.
(www.oecd-nea.org)
- OECD/NEA, 2020a. NEA Policy Brief: Final Disposal of Radioactive Waste, June 2020.
(www.oecd-nea.org)
- OECD/NEA, 2020b. Accelerator-driven Systems (ADS) and Fast Reactors (FR) in Advanced Nuclear Fuel Cycles, Note de Synthèse, August 2020.
(www.oecd-nea.org)
- OECD/NEA, 2021a. Strategies and Considerations for the Back End of the Fuel Cycle, February 2021.
(www.oecd-nea.org)
- OECD/NEA, 2021b. Small Modular Reactors: Challenges and Opportunities, April 2021.
(www.oecd-nea.org)
- OECD/NEA, 2021c. Advanced Nuclear Reactor Systems and Future Energy Market Needs, December 2021.
(www.oecd-nea.org)
- OPG, 2020. “OPG resumes planning activities for Darlington New Nuclear,” OPG news release, November 13, 2020.
(www.opg.com)
- OPG, 2021. “OPG advances clean energy generation project,” OPG news release, December 2, 2021.
(www.opg.com)
- OPG, 2022. “OPG applies to Canadian Nuclear Safety Commission for Licence to Construct,” OPG news release, October 2022.
(www.opg.com)
- OPG, Bruce Power, NB Power and SaskPower, 2021. Feasibility of Small Modular Reactor Development and Deployment in Canada, March 2021.
(www.opg.com)
- Posiva, 2021. Safety Case for the Operating Licence Application: Biosphere Radionuclide Transport and Dose Modelling. Report prepared by Posiva Oy. POSIVA 2020-24, December 2021.
(www.posiva.fi)
- RED-IMPACT, 2008. RED-IMPACT: Impact of Partitioning, Transmutation and Waste Reduction Technologies on the Final Nuclear Waste Disposal – Synthesis Report. FP6 Contract No: FI6W-CR-2004-002408. Forschungszentrum Jülich GmbH, September 2007.
- Reuters Events, 2022. 11th International SMR & Advanced Reactor Summit 2022, May 24-25, 2022, Atlanta, Georgia, United States.
(<https://reutersevents.com>)
- RWM, 2017. Review of Alternative Radioactive Waste Management Options. Report # NDA/RWM/146, prepared by Radioactive Waste Management Ltd., United Kingdom, March 2017.
(www.gov.uk/government/organisations/radioactive-waste-management)
- Sandia, 2009. Deep Borehole Disposal of High-Level Radioactive Waste. Report prepared by Sandia National Laboratories. SAND2009-4401, July 2009.
(www.sandia.gov)
- Sandia, 2011a. Generic Repository Design Concepts and Thermal Analysis (FY11). Report prepared by Sandia National Laboratories. SAND2011-6202, August 2011.
(www.sandia.gov)

- Sandia, 2011b. Reference Design and Operations for Deep Borehole Disposal of High-Level Radioactive Waste. Report prepared by Sandia National Laboratories. SAND2011-6749, October 2011.
(www.sandia.gov)
- Sandia, 2012a. Influence of Nuclear Fuel Cycles on Uncertainty of Geologic Disposal. Report # FCRD-UFD-2012-000088, prepared for the United States Department of Energy Used Fuel Disposition Campaign by Sandia National Laboratories, July 2012.
(www.energy.gov)
- Sandia, 2012b. Deep Borehole Disposal of Nuclear Waste: Final Report. Report prepared by Sandia National Laboratories. SAND2012-7789, September 2012.
(www.sandia.gov)
- Sandia, 2012c. Research, Development, and Demonstration Roadmap for Deep Borehole Disposal. Report prepared by Sandia National Laboratories. FCRD-USED-2012-000269, SAND2012-8527P, August 2012.
(www.sandia.gov)
- Sandia, 2012d. Site Characterization Methodology for Deep Borehole Disposal. SAND2012-7981, September 2012.
(www.sandia.gov)
- Sandia, 2013. Deep Borehole Disposal Research: Demonstration Site Selection Guidelines, Borehole Seals Design, and RD&D Needs. SAND2013-9490P, October 2013.
(www.sandia.gov)
- Sandia, 2014a. Deep Borehole Disposal Research: Geological Data Evaluation, Alternative Waste Forms, and Borehole Seals. SAND2014-17430R, September 2014.
(www.sandia.gov)
- Sandia, 2014b. Project Plan: Deep Borehole Field Test. SAND2014-18559R, September 2014.
(www.sandia.gov)
- Sandia, 2015a. Handling and Emplacement Options for Deep Borehole Disposal Conceptual Design. Report prepared by Sandia National Laboratories. SAND2015-6218, July 2015.
(www.sandia.gov)
- Sandia, 2015b. Deep Borehole Field Test: Characterization Borehole Science Objectives. Report prepared by Sandia National Laboratories. SAND2015-4424R, June 2015.
(www.sandia.gov)
- Sandia, 2015c. Conceptual Waste Packaging Options for Deep Borehole Disposal. Report prepared by Sandia National Laboratories. SAND2015-6335, July 2015.
(www.sandia.gov)
- Sandia, 2015d. Active Suppression of Drilling System Vibrations for Deep Drilling. Report prepared by Sandia National Laboratories. SAND2015-9432, September 2015.
(www.sandia.gov)
- Sandia, 2015e. Deep Borehole Field Test Requirements and Controlled Assumptions. Report prepared by Sandia National Laboratories. SAND2015-6009, July 2015.
(www.sandia.gov)
- Sandia, 2016. Deep Borehole Disposal Safety Analysis. Report prepared by Sandia National Laboratories. SAND2016-10949R, September 2016.
(www.sandia.gov)
- Sandia, 2019. Deep Borehole Disposal Safety Case. Report prepared by Sandia National Laboratories. SAND2019-1915, February 2019.
(www.sandia.gov)

- SaskPower, 2022a. "SaskPower selects the GE-Hitachi BWRX-300 Small Modular Reactor technology for potential deployment in Saskatchewan," SaskPower news release, June 27, 2022.
(www.saskpower.com)
- SaskPower, 2022b. "Two areas identified for further study to host Small Modular Reactor," SaskPower news release, September 20, 2022.
(www.saskpower.com)
- SFEN, 2022. GLOBAL 2022, International Perspectives on Nuclear Fuel Cycle, New Nuclear Perspectives in the Energy Supply Crisis and Climate Emergency, July 6-8, 2022, Reims, France.
(www.sfen.org/evenement/global-2022)
- SKB, 1989. Storage of Nuclear Waste in Very Deep Boreholes: Feasibility Study and Assessment of Economic Potential. Part I: Geological Considerations. Part II: Overall Facility Plan and Cost Analysis. SKB Technical Report 89-39, December 1989.
(www.skb.se)
- SKB, 1998. The Very Deep Hole Concept – Geoscientific appraisal of conditions at great depth. SKB Technical Report 98-05, June 1998.
(www.skb.se)
- SKB, 2000. Very deep borehole: Deutag's opinion on boring, canister emplacement and retrievability. SKB Report R-00-35, May 2000.
(www.skb.se)
- SKB, 2004. Recent geoscientific information relating to deep crustal studies. SKB Report R-04-09, January 2004.
(www.skb.se)
- SKB, 2013a. Review of geoscientific data of relevance to disposal of spent nuclear fuel in deep boreholes in crystalline rock. SKB Report P-13-12, September 2013.
(www.skb.se)
- SKB, 2013b. Radiological consequences of accidents during disposal of spent nuclear fuel in a deep borehole. SKB Report P-13-13, July 2013.
(www.skb.se)
- SKB, 2013c. Modelling of thermally driven groundwater flow in a facility for disposal of spent nuclear fuel in deep boreholes. SKB Report P-13-10, September 2013.
(www.skb.se)
- SMR Action Plan, 2020. Canada's Small Modular Reactor SMR Action Plan.
(smractionplan.ca)
- SNETP, 2012. The Sustainable Nuclear Energy Technology Platform – Strategic Research Agenda – Molten Salt Reactors.
(www.snetp.eu)
- SNETP, 2015. The Sustainable Nuclear Energy Technology Platform – Deployment Strategy.
(www.snetp.eu)
- SNETP, 2018. The Sustainable Nuclear Energy Technology Platform – Advanced Lead Fast Reactor European Demonstrator (ALFRED Project).
(www.snetp.eu)
- SNETP, 2021. The Sustainable Nuclear Energy Technology Platform – SNETP Strategic Research and Innovation Agenda, July 2021.
(www.snetp.eu)

- Triplett et al., 2012. PRISM: A Competitive Small Modular Sodium-Cooled Reactor. Paper by Brian S. Triplett, Eric P. Loewen and Brett J. Dooies, published in Nuclear Technology, vol. 178, May 2012.
(www.gehitachiprism.com)
- U.S. BRC, 2012. Blue Ribbon Commission on America's Nuclear Future: Report to the Secretary of Energy, January 2012.
(www.energy.gov/sites/prod/files/2013/04/f0/brc_finalreport_jan2012.pdf)
- U.S. DOE, 2014a. Project Plan: Deep Borehole Field Test. Report prepared by Sandia National Laboratories. FCRD-UFD-2014-000592, September 2014.
(www.doe.gov)
- U.S. DOE, 2014b. Assessment of Disposal Options for DOE-Managed High-Level Radioactive Waste and Spent Nuclear Fuel. October 2014.
(www.doe.gov)
- U.S. DOE, 2016. "Energy Department selects Battelle team for a deep borehole field test in North Dakota," Press release, January 5, 2016.
(www.energy.gov/articles/energy-department-selects-battelle-team-deep-borehole-field-test-north-dakota)
- U.S. DOE, 2017. "Studying the feasibility of deep boreholes," Press release, May 23, 2017.
(www.energy.gov/articles/studying-feasibility-deep-boreholes)
- U.S. NRC, 2012. Environmental Topical Report for Potential Commercial Spent Nuclear Fuel Reprocessing Facilities in the United States – Final Report, September 2012.
(www.nrc.gov)
- U.S. NWTRB, 2016. Technical Evaluation of the US Department of Energy Deep Borehole Disposal Research and Development Program. Prepared by the United States Nuclear Waste Technical Review Board, January 2016.
(www.nwtrb.gov)
- USNC, 2022. "McMaster University, Ultra Safe Nuclear Corporation, and Global First Power sign MOU to study deployment of Micro Modular Reactor (MMR®)," Ultra Safe Nuclear news release, December 11, 2022.
(www.usnc.com)
- von Hippel and Hayes, 2010. Deep Borehole Disposal of Nuclear Spent Fuel and High Level Waste as a Focus of Regional East Asia Nuclear Fuel Cycle Cooperation. Report prepared for The Nautilus Institute by David von Hippel and Peter Hayes, December 2010.
(www.nautilus.org)
- WNA, 2022a. World Nuclear Association Symposium 2022, September 7-9, 2022, London, United Kingdom.
(www.wna-symposium.org)
- WNA, 2022b. Supply of Uranium (updated June 2022). World Nuclear Association.
(<https://world-nuclear.org/information-library/nuclear-fuel-cycle/uranium-resources/supply-of-uranium.aspx>)
- WNN, 2021a. Estonia's geology suitable for deep borehole repository, February 1, 2021.
(www.world-nuclear-news.org/Articles/Estonias-geology-suitable-for-deep-borehole-reposi)
- WNN, 2021b. Slovenia considers deep borehole disposal, August 31, 2021.
(www.world-nuclear-news.org/Articles/Slovenia-considers-deep-borehole-disposal)

For more information,
please contact:

Nuclear Waste Management Organization
22 St. Clair Avenue East, Fourth Floor
Toronto, ON M4T 2S3, Canada
Tel.: 416.934.9814 Toll free: 1.866.249.6966
Email: contactus@nwmo.ca
Website: www.nwmo.ca

   @nwmoCanada

 /company/nwmoCanada

© 2023 Nuclear Waste Management Organization

